



Specifications:
 Current rating:1.0A AC/DC
 Voltage rating:250V AC/DC $\triangle F$
 Contact resistance:20m ohm max.
 Withstanding Voltage:500V AC/minute
 Insulation resistance:1000M ohm min.
 Temperature Rating:-40°C ~ +105°C

Materials:
 Insulator:PBT (UL94V-0)
 Contact :Copper Alloy
 Finish:Selective Gold Plated

How To Order

4401-XXSR-XX-XX $\triangle A$

- Blank:Black(Standard Color)
- GR:Gray;BU:Blue;WH:White $\triangle A$
- RD:Red;YL:Yellow;GN:Green $\triangle J$
- Blank Selective Gold Plated
- $\triangle A$ 03:Selective Gold Plated 3u"
- $\triangle H$ 08:Selective Gold Plated 8u"
- $\triangle H$ 15:Selective Gold Plated 15u"
- $\triangle H$ 30:Selective Gold Plated 30u"
- SR:With Strain Relief
- No. of Contacts

Dimension Information: $\triangle D$

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
6	12.30	5.08	30	42.78	35.56
8	14.84	7.62	34	47.86	40.64
10	17.38	10.16	36	50.40	43.18
12	19.92	12.70	40	55.48	48.26
14	22.46	15.24	44	60.56	53.34
16	25.00	17.78	50	68.18	60.96
18	27.54	20.32	56	75.80	68.58
20	30.08	22.86	60	80.88	73.66
24	35.16	27.94	64	85.96	78.74
26	37.70	30.48			

RoHS Compliant

J	26-DEC-2023	Add Color Option	Jamie	DRAWN: Leo	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15
I	01-Nov-2023	Add Plated Option	Lucy		
H	14-Jul-2022	Add Plated Option	Lucy	CHECKED: Jeremy Liu	UNIT: mm SCALE: 1:1
G	18-Dec-2019	Modify Tolerance	Jamie		
F	30-Oct-2013	ECN-CN1310004	Andrew	APPROVAL: MIKE WU	SHEET: 1 / 1
A	10-MAR-2008		Leo		
REV	DATE	FILE	BY		PROJECTION: \odot \square



Neltron Industrial Co., Ltd.

DESCRIPTION:
2.54MM Flat Cable IDC Socket With Strain Relief

PART NO:
4401-XXSR-XX-XX $\triangle A$

SIZE

A4